



CROCOPY RESOLUTION TEST CHART-



OFFICE OF NAVAL RESEARCH

Contract N00014-84-K-0557

R&T Code 413b002

Technical Report No. 1

Photoassisted Reaction of H₂ with CO₂ over Solid Catalysts

by

Norman N. Lichtin, K.M. Vijayakumar and B.I. Rubio

Accepted for Publication

in the

Journal of Catalysis



Boston University Boston, MA 02215

November 14, 1986

Reproduction in whole or in part is permitted for any purpose of the United States Government

This document has been approved for public release and sale; its distribution is unlimited.

86 11 25 305

SECURITY CLASSIFICATION OF THIS PAGE					
	REPORT DOCUI	MENTATION	PAGE		
18. REPORT SECURITY CLASSIFICATION		16. RESTRICTIVE	MARKINGS		·
Unclassified/Unlimited					
2a. SECURITY CLASSIFICATION AUTHORITY	3. DISTRIBUTION	/AVAILABILITY	OF REPORT		
2b. DECLASSIFICATION / DOWNGRADING SC	Unlimited	i			
4. PERFORMING ORGANIZATION REPORT N	IUMBER(S)	5. MONITORING	ORGANIZATION	REPORT NUM	IBER(S)
Technical Report No. 1					
6a. NAME OF PERFORMING ORGANIZATION		7a. NAME OF M	ONITORING ORG	ANIZATION	amiatry Division
Dept. of Chemistry	(If applicable)	Uffice of	r navai kes	earch, ch	emistry Division
Boston University					
6c. ADDRESS (City, State, and ZIP Code)		76. ADDRESS (Cr	- · · · · · · · · · · · · · · · · · · ·		
Boston, MA 02215		Arlington	n, VA 22217		
8a. NAME OF FUNDING/SPONSORING	8b. OFFICE SYMBOL	9. PROCUREMEN	T IAICTOI IAICAIT II	DENTIFICATIO	AL AULIANDED
ORGANIZATION	(If applicable) Code 413	l	N00014-84-		IN INCIMIDEN
8c. ADDRESS (City, State, and ZIP Code)	Code 413	10. SOURCE OF			
		PROGRAM	PROJECT	TASK	WORK UNIT
See 7b		ELEMENT NO.	NO.	NO.	ACCESSION NO.
11. TITLE (Include Security Classification)		<u> </u>	<u> </u>	ــــــــــــــــــــــــــــــــــــــ	
Photoassisted Reaction of	H ₂ with CO ₂ over So	lid Catalyst	s		
12. PERSONAL AUTHOR(S)	1 W M Dubia	Present T			
Lichtin, Norman N., Vijaya					
13a. TYPE OF REPORT 13b. TI Technical FROM	IME COVERED I TO	14. DATE OF REPO 1986. No	RT (Year, Monti vember 14	1, <i>Day</i>) 15. P	AGE COUNT
16. SUPPLEMENTARY NOTATION					
Accepted for publication i	in Journal of Cataly	sis, Oct. 16	, 1986		
17. COSATI CODES	18. SUBJECT TERMS (Continue on revers	e if necessary ar	nd identify by	block number)
FIELD GROUP SUB-GROU					nation of CO ₂
		•	·		~
19. ABSTRACT (Continue on reverse if nec	essary and identify by block r	umber)			
See attached page.					
{					
			•		
20 DISTRIBUTION / AVAILABILITY OF ABST		21. ABSTRACT SE	CURITY CLASSIF	CATION	
UNCLASSIFIED/UNLIMITED SAM	E AS RPT. DTIC USERS		lfied/unlim		
223. NAME OF RESPONSIBLE INDIVIDUAL		226 TELEPHONE		de) 22c. Offi	CE SYMBOL
Norman N. Lichtin	92 A 99 A d. A	(617) 353			
DD FORM 1473, 84 MAR	83 APR edition may be used up All other editions are o		SECURITY	Y CLASSIFICAT	TION OF THIS PAGE

The state of

+or-

er a-Fe203, Zn-Fe

The dark and photoassisted reactions of CO2 with H2 over a-Fe203, Zn-Fe Oxide, Co-Mo-Al-oxide, Co-Mo-Ti-oxide, platinized La-Ni-oxide and platinized SrTiO3 have been investigated in the absence and presence of water vapor. Illumination was by a Hg-Xe-lamp at wavelengths above 350nm, The incident light flux, measured by ferrioxalate actinometry, was (1.0240.08)x1524 photons/sec. Reactants in the ratio of H_2 : $CO_2 = 2:1$ were passed once over dry films of powdered catalysts at 30°C and latm with contact times of 1/2 or 1min. Products were analysed by gas chromatography. No reaction took place rates of production of products were in the absence of catalyst. Catalyzed constant over the 22hr periods investigated. CO was the only product obtained in significant amounts in the dark. Under illumination, rates of formation of CO increased by a factor of 2 - 4.5. CH4 was the only other product of the photoassisted reaction in the absence of water vapor, with yields less than 0,2mole% of those of CO. In the presence of water vapor (3 mole% of supplied CO2), formic acid was produced at rates up to 19mole% the rate of formation of CO, along with minor amounts of CH4, CH2O and CH3OH, all produced at rates less than 0.2mole% that of CO. The highest photoassisted yields were obtained over Co-Mo-Al oxide, with efficiency of conversion of incident photons into products around 0.35molecule of product/incident photon. The corresponding estimated quantum yield was 1 molecule of product/absorbed photon ver this catalyst, in the presence of water vapor and under the arbitrary conditions employed, the observed fractional conversion of CO2 to products was\about ten times the value for gas-phase equilibrium calculated from thermodynamic data.



Access	sien For		_
NTIS	$G^{\tau_{\ell}} \otimes F X$		
DTIC 3			
Undern			
Justi			
By.			
Distr	a) 55:597/		
Avai	1 - 4 - 14 -	, · ` · · g	
	Avel, M	11/C*	
Dist	1 1 2 2 2 3	, `	
	•		
1	-		
'	1 i		

PHOTOASSISTED REDUCTION OF ${\tt CO_2}$ BY ${\tt H_2}$ OVER METAL OXIDES IN THE ABSENCE AND PRESENCE OF WATER VAPOR

by

Norman N. Lichtin, K. M. Vijayakumar and Bruno I. Rubio Dept. of Chemistry, Boston University, Boston, MA 02215

1. INTRODUCTION

We have previously reported initial results of an investigation of the photoassisted reduction of CO₂ by H₂ over a-Fe₂O₃, Zn-Fe-oxide, platinised La-Ni-oxide, Co-Mo-Al-oxide and Co-Mo-Ti-oxide in the absence and presence of water¹. We now report more extensive quantitative yield data for the same reactant systems with the same catalysts, as well as with platinised SrTiO₃, and the relationship of yields to incident and absorbed light energy. The data are compared with calculated gas phase equilibrium compositions and it is shown that, with the most active catalyst, Co-Mo-Al-oxide, photoassisted consumption of CO₂ in the presence of water vapor under arbitrarily chosen conditions was about 10 times greater than would be expected from gas-phase equilibration. Over this catalyst, the observed efficiency of use of incident photons was O.35 molec. of photoproduct per incident photon, corresponding to an estimated quantum yield of 1 molec. of photoproduct per photon absorbed by the catalyst.

2. MATERIALS AND METHODS

100000

2.1 Catalysts and Reactants Preparations of the previously reported catalysts and the sources and grades of the reagents used in these preparations and of

- H₂, Ar and CO₂ were as described previously.¹ High-purity He was supplied by Linde and Co. Pfaltz and Bauer research grade SrTiO₃ was platinized by treatment with O.1wt% aqueous chloroplatinic acid and dried in Ar at 200°C. As previously reported, the atomic ratio of Zn to Fe in Zn-Fe-oxide was 1:2 and that of La to Ni in La-Ni-oxide was 1:1. The composition of Co-Mo-Aloxide was 4.5wt% CoO, 15wt% MoO₃ and 80.5wt% Al₂O₃ while that of Co-Mo-Ti-oxide was 3.5wt% CoO, 10wt% MoO₃ and 86.5wt% TiO₂.
- 2.2 <u>Catalyst Films</u> Procedures for preparation of films were essentially as previously reported¹ except that He was used in place of N₂ for preconditioning films.
- 2.3 Reaction Apparatus Reactions were performed in 5x5x1cm or 4x7x2cm flow-through cells with flat major faces. A cell was connected to a gas flow system which provided reactants and carried the gas stream beyond the cell to a sampling valve coupled to the analytical system. The reaction cell was immersed in a water-bath thermostatted to ±0.05°C. Illumination was by a 200W Schoeffel Hg-Xe lamp equipped with a collimating lens system and mounted on an optical bench at a distance of 45cm from the cell. Short-wavelength ultraviolet and long-wavelength infrared were eliminated by, respectively, a 350nm Corning cut-off filter and the water bath. The light beam was split and the relative intensity of the light flux incident on the cell was continuously monitored with a #4382 Pacific Instruments photomultiplier connected to a recorder.
- 2.4 Reaction Conditions and Analyses of Products Reactions at the gas-solid interface were carried out at latm and 29.8°C by passing 59-64 mL/min of a mixture of H₂ and CO₂ at a molar ratio of, respectively, 1.85-2.13 to 1 for 3 to 22 hr. Condensible products were trapped in 10-20mL of water maintained at

O°C. Water vapor, when present, was at a molar ratio of 0.03 to 1 relative to CO2. Collection of condensible products and sampling of the reacted gas stream were started 30min after reaction was begun. Products were analyzed with a Perkin Elmer Sigma 300 gas chromatograph equipped with gas-sampling and column-switching valves, thermal conductivity and flame ionization detectors in series, and a Perkin Elmer LCI-100 computing integrator. Products trapped in water were analyzed on a Porapak-N column while products sampled from the gas stream downstream from the ice-trap were analyzed on Porapak-N and MS-5A columns, used in series with column switching. Formation of formic acid was confirmed spectrophotometrically using a Cary 210 instrument. Formaldehyde was determined by the chromotropic acid method3. Production of CO was qualitatively confirmed by the NBS Pd-silicomolybdate method4. 2.5 Actinometry The incident light flux was measured by ferrioxalate actinometry⁵ and the resulting data was used to calibrate the on-line photometer. Potassium oxalate monohydrate was Baker Analyzed Reagent, ferric chloride hexahydrate and sodium acetate trihydrate were both Fisher ACS Reagent grade, and phenanthroline monohydrate was Smith ACS Reagent grade. A 350-480nm band-pass filter was used in optical series with a 350nm cut-off filter to isolate the lamp flux at 350-480nm. The only significant components of the Hg-Xe lamp emission at 350-480nm are the mercury bands at 366, 405 and 436nm. In addition, the filters passed some light at wavelengths above 700nm. The total flux from the lamp which was incident on the cell was calculated from the actinometric data, the known characteristics of the filters and the known emission spectrum of the lamp. Four replicate measurements gave a value for the total lamp flux from 350-1000nm of (1.02±0.08)x10¹⁷ quanta/sec. The uncertainties in calculating the total flux from the actinometric data are

成立の時間的五十二十八日の日本

probably greater than the quoted standard deviation which was calculated from the experimental reproducibility. Based on the above value of the flux and the illuminated area of the cell, 7.1cm^2 , the spatially averaged flux was 1.4×10^{16} quanta/sec-cm². Fluctuations calculated from variations in photometer readings were neglible.

3. RESULTS

- 3.1 Products from Reaction of CO₂ with H₂ in the Absence of Water Vapor No products were detectable from reaction in the dark or under illumination in the absence of any catalyst. Yields of products formed in the presence of catalysts are summarised in Table 1. CO was the major product formed over all the catalysts and CH₄ was the principal minor product. Formic acid was not detectable in the absence of water vapor. All the catalysts which were investigated promoted reduction in the dark. Yields increased by a factor of 2-4.5 upon illumination of catalyst films, demonstrating that photoassisted reaction occurs with all the catalysts. Yields of CO were measured after both 3hr and 20-22hr of illumination. With all the catalysts, the average rate of production of CO, i.e., the total yield divided by the period of illumination, was independent of the period of illumination, indicating that catalytic activity remained constant for at least 20-22hr.
- 3.2 Products from Reaction of CO₂ and H₂ in the Presence of Water Vapor No product was detectable in the dark or under illumination in the absence of any catalyst. Results obtained in the presence of water vapor, summarized in Table 1, were independent of whether the reaction time was 3hr or 20-22hr. The presence of water vapor had little effect on dark yields of CO except over Co-Mo-Ti-oxide, where a 14% decrease was observed. Methane, in trace amounts, was the only product other than CO which was detected in the dark reaction.

Under illumination, yields of formic acid corresponding to 6.8-19mole% of the yields of CO were obtained. With all the catalysts except one, the sum of the yields of formic acid and CO obtained under illumination differed by only 0.04-4.5mole% from the yield of CO obtained under illumination in the absence of water vapor. With platinised La-Ni-oxide, the sum of the yields of these two products corresponded to 21mole% more than the yield of CO in the absence of water vapor. Minor products which were also observed in the photoassisted reaction in the presence of water vapor included CH₄ corresponding to 0.2mole% or less of the yields of CO, CH₃OH corresponding to 0.01mole% or less of the yields of CO, and traces of formaldehyde.

3.3 Efficiencies of Chemical Use of Incident and Absorbed Photons The determination of the magnitude of the incident light flux is described in section 2.5, above. It is assumed here that the absolute error in the flux is no larger than 0.3×10^{17} quanta/sec. The estimated error in yields of products and their average rate of production is $\pm 5\%$, or less. Thus, it is assumed that efficiencies of use of incident photons given in this paper have a reliability of about $\pm 35\%$. Values of efficiencies of use of incident photons, $E_i = (\text{molec. of photo-prod./sec})/(\text{quanta incident/sec})$, calculated from the data of Table 1, are given in Table 2. Rates of formation of photo-products were obtained by subtracting rates of the dark reaction from corresponding rates under illumination.

For each of the six catalysts, values of E_i in the presence and absence of water vapor are similar. Over the entire range of the experiments, E_i varies from .06 (with Co-Mo-Ti-oxide in the presence of water vapor) to 0.37 (with Co-Mo-Al-oxide in the presence of water vapor). Although the absolute values of E_i are estimated to be uncertain to around $\pm 35\%$, only the uncertainty in product yields, i.e., $\pm 5\%$, is pertinent to their relative values.

An additional source of uncertainty enters into the estimate of quantum efficiencies, $E_q = (molec. of photo-product/sec)/(quanta absorbed/sec)$. Rather than measuring the rate of absorption of photons by the catalysts, it has been assumed that all incident photons with energies equal to or greater than the band-gap of a given semiconductor were absorbed. The corresponding values of absorbed photon flux were then calculated from the measured incident flux with the aid of the emission spectrum of the Hg-Xe lamp. Literature values 6 of the band gaps of a-Fe₂0₃ and SrTiO₃ were estimated to correspond to absorption of, respectively, 64% (2.2eV) and 25% (3.2eV) of the incident photon flux. The literature value of the band-gap of MoO3 (2.9eV) was used to estimate the fraction of incident light absorbed by the two cobalt-containing oxides as 38%. La-Ni-oxide, a narrow-band electronic conductor7, is assumed to absorb the entire incident photon flux. No data on the band-gap of Zn-Fe-oxide appears to be available. Values of $E_{\mathbf{q}}$ are presented in Table 3. It is noteworthy that the highest values of Eq, obtained with Co-Mo-Al-oxide in the presence and absence of water vapor, are indistinguishable from unity.

4. DISCUSSION

4.1 Evidence of Catalytic Action The probability of the metal oxides used in this research functioning as significant sources of reducing equivalents is small. With two exceptions, metallic Pt and Co(II), all the metals were present in their highest common oxidation states, namely, Fe(III), Zn(II), Mo(VI), Al(III), Ti(IV), La(III), Ni(II) and Sr(II). The possibility that either Pt, Co(II) or impurities were significant reactants can be evaluated from the number of reducing equivalents required to produce the observed yields. E.g., 5.9mmole of CO and formic acid were produced in 22hr of

photoassisted reaction over Co-Mo-Al-oxide in the presence of water vapor, corresponding to 11.8 millireducing equivalents. Assuming 200mg of catalyst (see section 2.2), the 4.5wt% of CoO present in it corresponded to only 0.12 millireducing equivalents. Similarly, the 4.6meq of reduced products obtained in 21hr of photoassisted reaction over α -Fe₂O₃ in the presence of water vapor can be compared with the 1.25mmole of the catalyst present in 200mg of this compound. Similar consideration of the data for all the catalysts demonstrates that in no case could a sustantial part of the observed products have resulted from reaction with catalyst or impurity.

- 4.2 Consumption of H₂ Data on consumption of H₂, which is summarized in Table 3, is based on yields of CO and HCO₂H, measured flow-rates of H₂ and the assumption that only CO and H₂O or HCO₂H were produced in the reaction. Utilization of H₂ appears to be inefficient. However, no effort was made to optimize it by, e.g., recirculating it in a closed system.
- 4.3 Implication of Estimated Quantum Yields The highest values of E_q recorded in Table 3 are 1.0 for Co-Mo-Al-oxide and 0.7 for TiO_2 . If it is assumed that both these values reflect conversion efficiencies which differ little from unity, they can provide some insight into the photoassisted process. The units of E_q are molecules of product produced per absorbed photon. However, CO_2 is actually reduced by 2 reducing equivalents. An electron-transfer mechanism in which one photon promotes transfer of two electrons is not plausible. More probable are mechanisms in which absorption of a photon by the catalyst results in activation of a sorbed molecule so that it then undergoes reaction. Photoactivation of sorbed CO_2 in this fashion is an example of such a process. A practical implication of the observed values of E_q is the possibility that, if quantum yields are independent of light

intensity at subtantially higher intensities, proportionally higher rates of reaction can be obtained.

4.4 Relationship between Photoassisted Yields in the Presence and Absence of Water The fact that photoassisted yields of CO in the absence of water differ little from the sum of photoassisted yields of CO plus HCO2H in the presence of water supports the conclusion that the principal effect of water is to divert part of the photoassisted reaction from production of CO to production of formic acid. However, the data provide no mechanistic inferences and do not provide a basis for concluding whether CO is a precursor of formic acid. 4.5 Comparison of Equilibrium Conversion with Photoassisted Conversion The reaction which produces CO is presumably the reverse of the water-gas shift reaction. Observed efficiencies for the conversion of CO2 can be compared with fractional conversions calculated from thermodynamic data for the gasphase water-gas shift reaction8. The equilibrium constant calculated for the formation of CO is 1.23x10⁻⁵ at 30°C. Percent conversions of CO₂, calculated from this value, are compared in Table 3 with conversion efficiencies obtained with the most active catalyst employed, Co-Mo-Al-oxide. No effort was made to establish equilibrium in the dark reaction or to achieve the photostationary state under illumination. Nevertheless, the fact that photoassisted conversion efficiency exceeds the value calculated for gas-phase equilibrium, and by a factor of about 10 in the presence of added water vapor, suggests that there is a large difference between the dark equilibrium and photostationary states and supports the possibility of obtaining subtantially higher efficiencies of conversion of CO2 and H2 by manipulation of conditions, e.g., residence time of reactants in the cell and intensity of illumination and area of catalyst surface accessible to light.

ACKNOWLEDGMENT

This work was supported in part by the Office of Naval Research.

REFERENCES

- 1. Vijayakumar, K.M., and Lichtin, N.N., J. Catalysis 90, 173 (1984).
- 2. Adams, G.E., and Hart, E.J., J.Amer.Chem.Soc. 84, 3996 (1962).
- 3. Lichtin, N.N., J.Phys.Chem. 63, 1449 (1959).
- 4. Sheperd, M., Anal. Chem. 19,77 (1947).
- 5. Calvert, J., and Pitts, J., "Photochemistry", John Wiley and Sons, Inc., New York, NY, 1966, pp.783-6.
- 6. Madelung, O., Ed., "Landolt-Bornstein, Numerical Data and Functional Relationships in Science and Technology, Vol. 17, Semiconductors, Subvolume g, Physics of Non-Tetrahedrally Bonded Binary Compounds III,", Springer-Verlag Berlin, 1980.
- 7. Galasso, F., "Structure and Properties of Inorganic Solids," Pergamon Press, New York, NY, 1970, p.217.
- 8. Weast, R.C., and Astle, M.J., Eds., *CRC Handbook of Chemistry and Physics*, CRC Press, Inc., Boca Raton, FL, 61st edition, 1980, pp.D67-D78.

TABLE 1 Average Rates of Production of Products in the Reaction of Flowing^a CO₂ and H₂ over Films of Metal Oxides^b

at 1 Atmc and 29.8°C

Catalyst	Photo- assisted	Average Rate of Production in the absence of (H ₂ 0)g µmole/hr		Average Rate of Production in presence of (H ₂ 0)g µmole/hr				
		CO	CH ₄	C0	CH ₄	HCO ₂ H	CH ₂ 0	СН30Н
a-Fe ₂ 0 ₃	No Yes	58 116		54 102	0.11	8.9	Tr	0.10
Zn-Fe-oxide	No Yes	110 234	0.29	114 215	Tr 0.36	20.1	Tr	0.11
Co-Mo-Al-oxide	e No Yes	64 280	0.41	59 267	Tr 0.41	19.3	Tr	0.21
Co-Mo-Ti-oxide	e No Yes	88 138	0.12	102 126	 Tr	14.8	Tr	0.07
Pt-La-Ni-oxide	e No Yes	102 158	0.21	108 160	0.22	30.8	Tr	0.15
Pt-SrTi03	No Yes	64 172	0.32	59 160	0.31	10.6	Tr	0.06

¹⁶⁻¹⁷ mmole/hr

b. 0.15-0.20 g. of finely ground catalyst in 25 or 28cm^2 films; c. Partial pressures: $C0_2$, 0.33 ±.02 atm; H_2 , 0.67 ±.04 atm; H_20 when present, 0.01 atm.

TABLE 2

Efficiencies of Utilization of H₂ and Photons in the Reaction of CO₂ with H₂ over Metal Oxides in the Absence and Presence of Water Vapor D

Catalyst	Water	Photo-			of Use
	Vapor	assisted	H ₂	Pho: E _i	tons E _q
α-Fe ₂ 0 ₃	No	No	0.06		
	No	Yes	0.11	0.10	0.15
	Yes	No	0.05		
	Yes	Yes	0.10	0.09	0.14
Zn-Fe-oxide	No	No	0.11		
	No	Yes	0.24	0.20	
	Yes	No	0.11		
	Yes	Yes	0.24	0.20	
Co-Mo-Al-oxide	No	No	0.07		
	No	Yes	0.28	0.34	0.98
	Yes	No	0.07		
	Yes	Yes	0.29	0.37	1.03
Co-Mo-Ti-oxide	No	No	0.09		
	No	Yes	0.14	0.08	0.23
	Yes	No	0.10		
	Yes	Yes	0.14	0.06	0.18
platinized La-Ni-oxide	No	No	0.10		
beergreed an ur aused	No	Yes	0.16	0.09	0.09
	Yes	No	0.11		
	Yes	Yes	0.19	0.14	0.14
platinized SrTiO3	No	No	0.07		
brantmened of 1202	No	Yes	0.17	0.18	0.71
	Yes	No	0.06		
	Yes	Yes	0.17	0.18	0.73

a. Efficiencies in the presence of water vapor are based on sums of the yields of CO and HCO_2H . Values of E_i and E_q are expressed in pure numbers, <u>not</u> in percent.

b. Conditions given in Table 1.

TABLE 3

Comparison of Observed Conversion of CO₂ over Co-Mo-Al-oxide at 30°C and 1min Residence Time with Gas-Phase Equilibrium Conversion^a

Concentrations of Reactants			% Conversion				
	n)		Calculated	Observed			
	CO ₂	${\tt H_2}$	${ t H}_{ extbf{2}}{ t 0}$	Equilibrium	Dark	Photoassisted	
	11.9	28.1		0.54	0.15	0.65	
	13.2	27.0	0.54	0.06	0.12	0.60b	

a. Conditions given in Table 1.

b. Based on sum of yields of CO and ${\rm HC}_2{\rm OH}$.

01/1113/86/2

TECHNICAL REPORT DISTRIBUTION LIST, GEN

	No.		No.
	Copies		Copies
Office of Naval Research Attn: Code 1113 800 N. Quincy Street Arlington, Virginia 22217-5000	2	Or. David Young Code 334 NORDA NSTL, Mississippi 39529	1
Dr. Bernard Douda Naval Weapons Support Center Code 50C Crane, Indiana 47522-5050	1	Naval Weapons Center Attn: Dr. Ron Atkins Chemistry Division China Lake, California 93555	1
Naval Civil Engineering Laboratory Attn: Dr. R. W. Drisko, Code L52 Port Hueneme, California 93401	1	Scientific Advisor Commandant of the Marine Corps Code RD-1 Washington, D.C. 20380	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	r 12 high quality	U.S. Army Research Office Attn: CRD-AA-IP P.O. Box 12211 Research Triangle Park, NC 27709	1
DTNSRDC Attn: Dr. H. Singerman Applied Chemistry Division Annapolis, Maryland 21401	1	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 19112	1
Dr. William Tolles Superintendent Chemistry Division, Code 6100 Naval Research Laboratory Washington, D.C. 20375-5000	1	Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232	1

DTZ